



## Product information sheet

- Product Name: **Park It Car Stop**
- Models: 6', 4', 3' long
- Manufacturer: GNR Technologies Inc., manufacturing division of Traffic Logix Inc.,  
990 Upton, Lasalle, QC H8R 2T9  
Tel.: (514) 366-6116, Fax: (514) 366-6440
- Product Description:
1. Material: compression molded composite of the 100% recycled rubber and polyurethane prepolymer
  2. Physical properties of the rubber composite:
    - a) Density 0.6 oz/cu in (ASTM C642)
    - b) Durometer Hardness 65A ± 7 (ASTM D2240)
    - c) Tensile Strength\* minimum 210 psi (ASTM D412)  
(\* main structural areas)
    - d) Compression deformation 10% at 70psi, 68°F (ASTM D575)
    - e) Brittleness at Low temperature: -40°F (ASTM D746)
    - f) Freeze and thaw when exposed to deicing chemicals no loss after 50 cycles (ASTM C672)
    - f) Coefficient of thermal expansion:  $8 \times 10^{-5}$  in/in/°F (ASTM C531)
    - g) Weathering 70 hours at 158°F (ASTM D573)
      - hardness retained 100% (± 5%)
      - compressive strength 100% (± 5%)
      - tensile strength 100% (± 5%)
      - elongation retained 100% (± 5%)
  3. Available models: 6', 4' and 3' long
  4. Basic dimensions and nominal weights as per attached drawings
  5. Finishing: Black with durable reflective yellow, blue or white molded in tape as per attached drawings
- Installation methods:
- a) with spikes 14" long (minimum diameter 1/2", recommended 5/8")
    - 4 spikes for 6' model
    - 3 spikes for 4' model
    - 2 spikes for 3' model
  - b) with the lag bolts 6" long with 3" long lead shields (minimum diameter 1/2", recommended 5/8")
    - 4 spikes for 6' model
    - 3 spikes for 4' model
    - 2 spikes for 3' model
  - c) with polyurethane adhesive (recommended PL Premium)

- 300 ml. per 6' model
- 200 ml. per 4' model
- 150 ml. per 3' model

Components: a) 100% recycled rubber from car and truck tires (NR, SBR)  
b) polyurethane prepolymer for rubber granules  
c) durable yellow, white or blue molded-in tape covered with the glass beads

Warranty: A three (3) year warranty is provided on the product and a 1 year warranty on the tape, as per the manufacturer's installation instructions.

Attached Drawings: 6' model, drawing No. 34PC02-3  
14" rebar spike, drawing No. 05SP01

03/06/2011